

# NJ A00/A0/A1/A2



## NJ A00/A0/A1/A2

Working principle	Electro-magnetic
DPI	100-12800dpi
Active area	1118X1524mm/914X1219mm/610X914mm/470X630mm
Connection port	RS-232/USB
Baud rate	150-19200
Power	220V AC+/-10%,50HZ,60HZ
Accuracy	0.2mm
Data rate	10-200PPS
Output format	31 types of industrial standard formats
Digitizer dimension	1715X1335X25mm/1415X1115X25mm/1145X850X25mm/845X650X25mm
Package dimension	1900X1480X150mm/1600X1250X150mm/1300X1000X150mm/1000X800X150mm
Environment	Temperature:-5°C - 50°C;Humidity:RH10-95% no Condensation
Gross weight	50KGS/34KGS/26KGS/23KGS

工作原理	电磁感应原理
分辨率	100-12800dpi
工作面积	1118X1524mm/914X1219mm/610X914mm/470X630mm
硬件接口	RS-232/USB
波特率	150-19200
电源	220V AC+/-10%,50HZ,60HZ
精度等级	0.2mm
数据传输率	10-200PPS
数据输出格式	31种工业标准格式
外形尺寸	1715X1335X25mm/1415X1115X25mm/1145X850X25mm/845X650X25mm
包装尺寸	1900X1480X150mm/1600X1250X150mm/1300X1000X150mm/1000X800X150mm
环境要求	温度：-5°C - 50°C；湿度：RH10-95% 无冷凝
毛重	50KGS/34KGS/26KGS/23KGS